

# Acriche LED AW3221-01

Ηα ίαθάε οίθαιίαιέ ιέιυαάεά

Acriche ηάοοίαιέιαιύ ηάθέγ ηίαοεάεüíí θαϑθαίθαιά äëý èñííëüçíááíëý á ιθííüøéáííüð ηάοýò ιάθαιίίííí οίεά. Íáεάñòε ιθεíáíáíëý AW3221, AN3221, AW3220, AN3220, AN4240, AN4221, AN4222, AN4223, AN4224.

Íñííáííüá οάοίε÷áñéεά θάθαιεοάθèñòèèè ηάάοίαιέíáá:Part No.ColorVF[V]&Phi;v[Im]&Phi;I[lux]IOPT[mA]2&theta;½[Ú]TypeSpec.AN White3000K220 VAC18020020130PCB Data Sheet Íáεíáííááíεά, íñííáííüá ιάθαιíáθòüíθíεçáíáεèòáëüĐíçíεèòáíò 10θò.íò 20θò.

AN 3221-01

(òáíëí-ááëüé ~200Lm 4.0W 220VAC)SSC

\$7,50

+ áñòü á ίáεè÷èè

ííá

çàèàç

ííá

çàèàç

Íñííáííüá οάοίε÷áñéεά θάθαιεοάθèñòèèè ηάάοίαιέíáá:Part No.ColorVF[V]&Phi;v[Im]&Phi;I[lux]IOPT[mA]2&theta;½[Ú]TypeSpec.AN White6300K220 VAC21524020130PCB Data Sheet Íáεíáííááíεά, íñííáííüá ιάθαιíáθòüíθíεçáíáεèòáëüĐíçíεèòáíò 10θò.íò 20θò.

AW3221-01

(ááëüé 215Lm 4.0W 220VAC)

SSC

\$7,50

+ áñòü á ίáεè÷èè

\$7,00

+ áñòü á ίáεè÷èè

\$6,50

+ áñòü á ίáεè÷èèÍðè ιιòíáüò çàèàçàò οóí÷íýεòá οáíí, ηέεάεè Ááñ ιθëýοíí óáëáýò!

Áíεάά ááòáëüíóρ εíοíθíáòèρ

ííæíí ίáεòè ίá ááá-ñáéòá èíííáíεè

Seoul Semiconductor

Íáo ίáíáοίáεííñòε ιθεíáíáíëý ηίαοεάεüííüð áθáεάáθíá äëý ιεòáíëý ηάάοίαιέíáá.

Áεëρ÷ááí AW3221-01 á ηάòü ιάθαιίίííí οίεά 220 áíëüò!

Èèü íáíí óñéíáεά.

Íáíáοίáεíí ιθááááθèòáëüíí çáèθáíεòü ηάάοίαιέíá Acriche ίá θááεàòíθá äëý ίááñíá÷áíëý ιιòεíáëüííáí óáíéíáíáí θáæéíá ýéñíεòáòá

Đáèííáíáóáíüé ιθíεçáíáεèòáëáí íεíεíáëüííüé θαçíáð θááεàòíθá äëý íòεáæááíëý ηάάοίαιέíáá ηíñòááëýáò 44mm\*44mm.

Είτε:-άνοαί νάαοίαιείαί, ιίάεεπ:-άαιύο ιάδαεεάεüí ê ñàè 220 VAC ñíáαδθáίí íá ιάδαίε:-άίí.

Áíεάά ιάδίαίúά δάεííáíαòèè ìò ιðíεçáíäèòáεý ιí ñíáεπááίεπ óáííáδòóδíúò δάæèíá δαáíóú ñáαοíαιείαί ýοίε ñáðèè ιðεάάááú

### ΕΙΕΕÈÌÀÒÍΘÍÚÁ ÈÈÍÇÙ

Íòèè:-íáy ίíáíñòù.

Ááñü ðýá èèίç äéý ñáαοíαιείαί P4,P7,Acriche, ιðíεçáíäèìúò Sekonix!

#### P7 LENS SERIES-1

Lens Symbol : PMMA

À1 deg-15°

À3 deg-25°

(Dimensions: ó 37,18mm \*20.18mm) Äéý ñáαοíαιείαί Seoul Semiconductor:Z-power Đ7 (W724c0) è Acriche (AW3221-01) Íàèì ιάδàíáòðúíðíεçáíäèòáéüíò 1 øò.íò 5-10 øò.íò 30 øò.

Collimate Lens for LED(s) Seoul Semiconductor À1 deg-15°

áñòù á íàèè:-èè

SEKONIX Íàèìáííááíεά, ίñííáíúá ιάδàíáòðúíðíεçáíäèòáéüíò 1 øò.íò 5-10 øò.íò 30 øò.

Collimate Lens for LED(s) Seoul Semiconductor À3 deg-25°

áñòù á íàèè:-èè

#### SEKONIX\$2,75\$2,60\$2,50P7 LENS SERIES-2

Lens Symbol : PMMA

Lens NARROW deg-10°

Lens WIDE deg-35°

Lens ELLIPTICAL X deg-45° & Y deg-25°

(Dimensions: ó 38,00mm \*18.59mm) Äéý ñáαοíαιείαί Seoul Semiconductor: Z-power Đ7 (W724c0) è Acriche (AW3221-01) Íàèì ιάδàíáòðúíðíεçáíäèòáéüíò 1 øò.íò 5-10 øò.íò 30 øò.

Collimate Lens for LED(s) Seoul Semiconductor Lens NARROW deg-10°

áñòù á íàèè:-èè

SEKONIX\$2,75\$2,60\$2,50Íàèìáííááíεά, ίñííáíúá ιάδàíáòðúíðíεçáíäèòáéüíò 1 øò.íò 5-10 øò.íò 30 øò.

Collimate Lens for LED(s) Seoul Semiconductor Lens WIDE deg-35°

íáo á íàèè:-èè

