

# Ãéáêèà ñááòíäèíáíúá äáíòú

WWW.SOHAN.COM.UA

## ÃÉÁÊÈÀ ÑÁÁÒÍÄÈÍÁÍÚÁ ÄÁÍÒÚ

Ëçýúíáý äéáéäý äáðíáòè÷íáý äáíòà

• Çàíáíà íáííà á íáðóæíé äáêèàíà

• Ñááòíáíà íòíðíéáíèà á óñéíáèýõ ñ ííáúøáííé

âèàæííòùþ

• Ííäñááòèà äáêèàííúó áóéá, ñèíáíéíá, èíáíòèííá,

âúááñíè

• Èáíäøàðòíáý ííäñááòèà

• Ííäñááòèà á ñáéíá áàòííáèèý, á èíèáñíúó àðèáð, ííäñááòèà òíðííçúó äèñéíá íáðááíèð òáð áàøááí àáòí, è òí.\*

Ãéáéäý á ííáðá÷íí íáíðááèáíèè, èáááèúíí ííáðíáèð äèý ñíçááíèý íááíèñáé è ðèñóíéíá. Èííñðóéòèáíí áúííéíáíà á äèáá øéáéòà çà íðíèçáíáýò íáðáááèèð òáð è óííáðáé áàòííáèèáé. Óñòáíááèèááðò äáñíè÷èè, èíèúòà, áóáè è íðí÷èà èðèáíèèáéíúá ýéáíáíóú.

Íáúèà íàðáíáòðú

• Èáíòà ñ 5í òèèéíáðè÷áñèèèè ñááòíáèíáíè

• Ííèðúòèá - ñèèèèíí

• Ðàçíáð 96507012íí

• Óáíè 180°

Íðèíáðú èñííèúçíááíèý äáíòú Waterproof (IP67).

Ãáííáý áíáííáíðííèòááíáý äáíòà èíííèáèòáòñý òáèæá äáðíáòè÷ííè ðàçúáíáè íà èííóáð "íáíà" "íàíà" (without waterproof connect) ñááòíáèíáíúá äèý íáèñèíáèèúííáí ðáññáèèáíèý ñááòíáíáí ííòíèà.

Í÷áíú óáíáíà äèý ñíçááíèý áíííéíèðáèúíúó ñááòíáíúó ýòðáèòíá áíóððè áàòííáèèúíúó òáð.Íðíèçáíáèòáèú: Hongli Opto-Electronic (H

B level uses high brightness and low degradation LEDs, with one year free warranty service íàèíáííáíèááòáò

ñáá÷áíèýíáí-

ðýæáíéá

VDCÍíððááèýáíáý

ííúííòú

1-áí íáòðà

äáíòúÈíè-áí

ñááòíáèíáíá

íà 1í.

äáíòúÑááòíáíé

ííòíè

1-áí

íáòðà

äáíòúÓáíè

èçèó÷áíèý Óáíà çà

1í. äáíòú

waterproof

IP-67

USD íåèè-èå HL-4H8H159 W96K23C4-12 Áåëúé-ðíëíáíúé 12Vdc4.0W96 Led d=5mm~100 Lm~180°

íæèåååòñý HL-4H8H159 WW96K23C4-12 Áåëúé-ðáíëúé 12Vdc4.0W96 Led d=5mm~100 Lm~180° no HL-4H8H190 B96K23C1  
Ñèíèé 12Vdc4.0W96 Led d=5mm~42 Lm~180° ï çàíðíñóyes HL-4H8H190 V96K23C1-12 Ôèíèàòíáúé 12Vdc4.0W96 Led d=5mm  
4H8 G96K23C4-12 (without waterproof connector) Çåëáíúé 12Vdc4.0W96 Led d=5mm~90 Lm~180° ï çàíðíñó

yes HL-4H8 Y96K23C4-12 (without waterproof connector) Æåëòúé 12Vdc4.0W96 Led d=5mm~44 Lm~180° ï çàíðíñóyes HL-4H8  
A96K23C4-12 Íðáíæååúé 12Vdc4.0W96 Led d=5mm~44 Lm~180° no HL-4H8 R96K23C4-12 (without waterproof connector)  
Ëðåñíúé 12Vdc4.0W96 Led d=5mm~45 Lm~180°

íæèåååòñý WWW.SOHAN.COM.UA

Waterproof Íðåèðåñí çàðåèííáííáíååàøåý ñååý ñååòíæèíáíåý éáíòà èç 18 ñååòíæèíáíåý ñòàòè-ííáí ðàçíáðà - 30ñí ñ íðíáíååè è ðàç

Í-áíú ýååñòè-íáý, íåèà-áííåý á íðíçðà-íúé ñèèèéíí, ñíòååòñòåáííí - áííáíáíðííèòååíáý. Óáíè ðåññååàíèý ñååòíáííí ïòíèà ïðýåè

B level uses high brightness and low degradation LEDs, with one year free warranty service Áåëúé-ðíëíáíúé FlexibleStripe-  
18LED 30CM 12V >íàò â íåèè-èè

Ñèíèé 468-472nm FlexibleStripe-18LED 30CM 12V >3,00\$

Çåë, íúé 521-525nm FlexibleStripe-18LED 30CM 12V >3,00\$

Ëðåñíúé 636-645m FlexibleStripe-18LED 30CM 12V >3,00\$

Íðáíæååúé 595-600nm FlexibleStripe-18LED 30CM 12V >3,00\$

Æåëòúé 586-590nm FlexibleStripe-18LED 30CM 12V >3,00\$

Ýååèååèáíò áðèáíááíé óáíú íà íðíáóèòèð ïðåååýåòñý ï èííáð-áñèííó éóðñó íà ííáíò ïñóúåñòåéáíèý íèàòååà. Á íðåáíí èíðíðíà  
Ëíðíðíàòèý ðåèèáííáí òàðåèòáðà, íåèè-èå è óáíú íåñòàòè-íúé è ððååòòò áíííèíèòåèííáí óòí-íáíèý.

Ðíçíè-íáý è ïòíáåý íðíååà á Ëèååå íà ðúíèá "Ðååèèèèèèèèèè"  
íà òíðáíáúó íåñòàò 594-598. (Ëàðåååååå Áà-è, óè. Óøèííèíáí, 4).  
Áíñòååèà çåèàçíá á áðóåèá áíðíåå Óèðåèíú á òå-áíèè 2-ò áíáé.  
Ìèíèíáèííáý ñóííà çåèàçà - íáíååðèåååòñý èíèèèèèèèèèíí.